




Inch size series Zöllige Kugellager



Bore Diameter d	Outer Diameter D	Radius r _{min}	Width B	Open	Double Shield	Width B1	Basic Load Rating Cr(N)	Basic Static Load Rating Cor(N)	Max. Speed	
									Grease	Oil
									x1000 rpm	
1.984	6.235	0.099	2.380	R1-4	R1-4ZZ-	3.571	284	96	67	80
2.380	4.762	0.099	1.588	R133	R133ZZ	2.380	144	53	80	95
-	7.938	0.149	2.779	R1-5	R1-5ZZ	3.571	552	176	60	71
3.175	6.350	0.099	2.380	R144J	R144JZZS	2.779	311	110	67	80
-	6.350	0.099	2.380	R144	R144ZZ	2.779	284	96	67	80
-	7.938	0.099	2.779	R2-5	R2-5ZZ	3.571	558	180	60	67
-	9.525	0.149	2.779	R2-6	R2-6ZZ	3.571	640	227	53	63
-	9.525	0.045	3.967	R2	R2ZZ	3.967	631	219	56	67
-	12.700	0.045	4.366	R2A	R2AZZ	4.366	640	227	53	63
3.967	7.938	0.099	2.779	R155	R155ZZS	3.175	359	150	53	63

Bore Diameter d	Outer Diameter D	Radius r _{min}	Width B	Open	Double Shield	Width B1	Basic Load Rating Cr(N)	Basic Static Load Rating Cor(N)	Max. Speed	
									Grease	Oil
									x1000 rpm	
4.762	7.938	0.099	2.779	R156	R156ZZ	3.175	359	150	53	63
-	9.525	0.099	3.175	R166	R166ZZ	3.175	709	272	50	60
-	12.700	0.045	3.967	R3	R3ZZ	4.978	1301	488	43	53
-	12.700	0.045	15.875	R3A	R3AZZ	4.978	1480	621	38	45
6.350	9.525	0.099	3.175	R168	R168ZZS	3.175	373	172	48	56
-	12.700	0.145	3.175	R188	R188ZZ	4.762	1082	442	40	50
-	15.875	0.099	4.978	R4	R4ZZ	4.978	1480	621	38	45
-	19.050	0.398	5.558	R4A	R4AZZ	7.142	2336	896	36	43
7.9838	12.700	0.149	3.967	R1810	R1810ZZ	3.967	542	276	40	48
9.525	15.875	0.149	3.967	R1038	R1038ZZ	3.967	815	411	28	31
-	22.225	0.149	5.558	R6	R6ZZ	7.142	3332	1422	32	38
12.700	19.050	0.149	3.967	R1212	R1212ZZ	3.967	898	524	21	26